



## QR28

by Burndy  
Catalog ID: QR28

Prop 65 Notice

Splice or Reducer, 3/0 Str. - 4/0 Str., Recommended Tightening Torque:  
250 IN-LB

## Product Details

### General

Connector Type	Splice;Reducer
Installation Torque Recommended in-lb	250 LBS/in
Material	Copper Alloy
Physical Attribute - Number of Screws	2
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Plating Type	Unplated
Trade Name	QIKLINK™
UPC	781810334515

### Dimensions

Dimension - B Length fraction	1-1/16 in
Dimension - B Length inch	1.06 in
Dimension - Height fraction	1-3/8 in
Dimension - Height inch	1.13 in
Dimension - L Length Overall mm	60 mm
Dimension - Length Overall inch	2.38 in
Dimension - Width fraction	1 in
Dimension - Width inch	1.00 in
Dimension - Width mm	25 mm

### Conductor Related

Conductor - Copper Solid Size A	3/0 AWG;4/0 AWG
Conductor - Copper Solid Size A Range	3/0 AWG-4/0 AWG
Conductor - Copper Solid Size B	3/0 AWG;4/0 AWG
Conductor - Copper Solid Size B Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Size A	3/0 AWG;4/0 AWG
Conductor - Copper Str Size A Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Size B	3/0 AWG;4/0 AWG
Conductor - Copper Str Size B Range	3/0 AWG-4/0 AWG

Conductor Type	<ul style="list-style-type: none"> <li>• CU C Str-Size A</li> <li>• CU C Str-Size B</li> <li>• CU C Solid-Size A</li> <li>• CU C Solid-Size B</li> </ul>
----------------	--

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
UL Listed	Yes

### Logistics

Minimum Pack Quantity	10
-----------------------	----

**For further technical assistance, please contact us**

**BURNDY Headquarters**  
 47 East Industrial Park Drive  
 Manchester, New Hampshire 03109

**Customer Service Hours:**  
 8 AM - 8 PM Eastern Monday-Friday  
 Emergency Service 24-hours/365 Days  
 Phone: 1-800-346-4175  
 1-603-647-5299 (International)